

YAMAP0913US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of

Kean et al.

Serial No.: 10/803,292

Filed: March 18, 2004



Art Unit: 2872

Examiner: Unknown

For: PARALLAX BARRIER AND MULTIPLE VIEW DISPLAY

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1345

**TRANSMITTAL OF CERTIFIED COPY**

Attached please find the certified copy of the foreign application from which  
priority is claimed for this case:

Country: Great Britain  
Application Number: 0306516.6  
Filing Date: March 21, 2003

SIGNATURE OF ATTORNEY

Reg. No. 34,243  
Tel. No. (216) 621-1113

Mark D. Saralino  
**RENNER, OTTO, BOISSELLE & SKLAR, L.L.P.**  
1621 Euclid Avenue  
Nineteenth Floor  
Cleveland, Ohio 44115





INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation and Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein together with the Statement of inventorship and of right to grant of a Patent (Form 7/77), which was also filed.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Dated 27 January 2004



# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road  
Newport  
South Wales  
NP9 1RH

1. Your reference

JSR.P52476GB

2. Patent application number

(The Patent Office will fill in this part)

0306516.6

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Sharp Kabushiki Kaisha  
22-22 Nagaike-cho  
Abeno-ku, Osaka 545  
Japan

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

Japan

8162869002

4. Title of the invention

"Parallax Barrier and Multiple View Display"

5. Name of your agent (if you have one)

Marks & Clerk

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

4220 Nash Court  
Oxford Business Park South  
Oxford OX4 2RU  
United Kingdom

7271125001 ✓

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)


8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

## Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document


Continuation sheets of this form	0
Description	19
Claim(s)	3
Abstract	1
Drawing(s)	17 + 17 

10. If you are also filing any of the following, state how many against each item.

### Priority documents

#### Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 2 —

Request for preliminary examination and search (Patents Form 9/77) 1 — 

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature 

Date

Marks & Clerk

20 March 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

John S. Robinson - 01865 397900


### Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

**Statement of inventorship and of  
right to grant of a patent**



The Patent Office

Cardiff Road  
Newport  
South Wales  
NP9 1RH

1. Your reference	JSR.P52476GB				
2. Patent application number (if you know it)	0306516.6				
3. Full name of the or of each applicant	Sharp Kabushiki Kaisha				
4. Title of the invention	"Parallax Barrier and Multiple View Display"				
5. State how the applicant(s) derived the right from the inventor(s) to be granted a patent	By virtue of employment of the inventors by Sharp Laboratories of Europe Limited (SLE), and by agreement with Sharp Kabushiki Kaisha.				
6. How many, if any, additional Patents Forms 7/77 are attached to this form? (see note (c))	1				
7. -	<p>I/We believe that the person(s) named over the page (and on any extra copies of this form) is/are the inventor(s) of the invention which the above patent application relates to.</p> <table border="0"> <tr> <td style="vertical-align: bottom;">Signature Marks &amp; Clerk</td> <td style="vertical-align: bottom;">Date</td> </tr> <tr> <td style="text-align: center;"></td> <td>20 March 2003</td> </tr> </table>	Signature Marks & Clerk	Date		20 March 2003
Signature Marks & Clerk	Date				
	20 March 2003				
8. Name and daytime telephone number of person to contact in the United Kingdom	John S. Robinson - 01865 397900				

**Notes**

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

KEAN, Diana Cynthia  
8 Pyrton Lane  
Watlington  
Oxfordshire  
OX49 5LX

Patents ADP number (if you know it):

8523336001

MONTGOMERY, David James  
7 Tudor Close  
Iffley  
Oxford  
OX4 4HB

Patents ADP number (if you know it):

7707821002

MATHER, Jonathan  
4 Oxeye Court  
Greater Leys  
Oxford  
OX4 7GQ

Patents ADP number (if you know it):

8523326001

Reminder

Have you signed the form?



Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

BOURHILL, Grant  
1 Mount Pleasant  
Stow on the Wold  
GL54 1AL

Patents ADP number (if you know it):

8307472001

JONES, Graham R  
8 Stanford Road  
Faringdon  
Oxfordshire  
SN7-7AQ

Patents ADP number (if you know it):

8427098001

**Reminder**

Have you signed the form?

Patents ADP number (if you know it):



DUPLICATE

## PARALLAX BARRIER AND MULTIPLE VIEW DISPLAY

The present invention relates to a parallax barrier and to a multiple view display including such a barrier. Such displays may be used when two or more different people need to see two or more different images on the same display screen. The viewing angle difference is preferably quite large (around 60 degrees) between viewers.

Such displays may also be used as three-dimensional (3D) displays, especially autostereoscopic displays. Such displays may be used in 3D mobile handsets, 3D games, 3D computer monitors, 3D laptop displays, 3D workstations and 3D professional imaging (e.g. for medical, design or architectural usage). In some 3D displays, it is necessary to increase the eye separation distance for a particular viewing distance or decrease the viewing distance for a particular eye separation. Both of these cases require a wider separation angle.

---

For many years now displays have been designed for multiple users and optimised so that viewers can see the same good image quality from different angles with respect to the display. This assumes that the multiple users require the same information from the display. However, there are many applications where it would be desirable for the individual users to be able to see different information from the same display. For example in an automobile, the driver may wish to view satellite navigation data while the passenger may wish to view a movie. If two displays were used in this instance, it would be possible for the driver to view the movie, which might be distracting, and providing two displays would take up extra space and increase cost. In computer games, each player may wish to view the game from his or her own perspective. This is currently done by each player viewing their unique perspective on individual screens. This takes up a lot of space and is not practical for portable games.

By showing more than one image to more than one user on one display, there can be a considerable saving in space and cost. This may be a desirable thing in airplanes where each passenger is provided with their own video screen. By providing one central

screen for two or more passengers but retaining the ability to select their own movie, there could be a considerable saving in cost, space and weight. There is also the ability to preclude the users from seeing each other's views. This might be a desirable thing in security applications such as banking or sales transactions as well as games.

In normal vision, the two human eyes perceive views of the world from different perspectives due to their separate location within the head. These two perspectives are then used by the brain to assess the distance to various objects in a scene. In order to build a display which will effectively display a three dimensional image, it is necessary to re-create this situation and supply a so-called "stereoscopic pair" of images, one to each eye of the observer.

Three-dimensional displays are classified into two types depending on the method used to supply the different views to the eyes. Stereoscopic displays typically display both of the images over a wide viewing area. However, each of the views is encoded, for instance by colour, polarisation state or time of display, so that a filter system of glasses worn by the observer can separate the views and will only let each eye see the view that is intended for it.

Autostereoscopic displays require no viewing aids to be worn by the observer but the two views are only visible from defined regions of space. The region of space in which an image is visible across the whole of the display active area is termed a "viewing region". If the observer is situated such that one of their eyes is in one viewing region and the other eye is in the viewing region for the other image of the pair, then a correct set of views will be seen and a three-dimensional image will be perceived.

For flat panel autostereoscopic displays, the formation of the viewing regions is typically due to a combination of the pixel structure of the display unit and an optical element, generically termed a parallax optic. An example of such an optic is a parallax barrier. This element is a screen with vertical transmissive slits separated by opaque regions. This screen can be set in front of a spatial light modulator (SLM) with a two-dimensional array of pixel apertures as shown in Figure 1.

The display comprises a transmissive spatial light modulator in the form of a liquid crystal device (LCD) comprising an active matrix thin film transistor (TFT) substrate 1, a counter substrate 2, a pixel (picture element) plane 3 formed by a liquid crystal layer, polarisers 4 and viewing angle enhancement films 5. The SLM is illuminated by a backlight (not shown) with illumination in the direction indicated by an arrow 6. The display is of the front parallax barrier type and comprises a parallax barrier having a substrate 7, an aperture array 8 and an anti-reflection (AR) coating 9.

The SLM is arranged such that columns of pixels are provided extending vertically for normal viewing with the columns having a horizontal pitch  $p$ . The parallax barrier provides an array 8 of apertures or slits with the slits being parallel to each other and extending parallel to the pixel columns. The slits have a width  $2w$  and a horizontal pitch  $b$  and are spaced from the pixel plane 3 by a separation  $s$ .

The display has an intended viewing distance  $r_o$  with left and right viewing windows 10 and 11 at the widest parts of the viewing regions defining a window plane 12. The viewing windows 10 and 11 have a pitch  $e$  which is generally made substantially equal to the typical or average human eye separation. The centre of each primary viewing window 10, 11 subtends a half angle  $\alpha$  to the display normal.

The pitch  $b$  of the slits in the parallax barrier is chosen to be close to an integer multiple of the pixel pitch  $p$  of the SLM so that groups of columns of pixels are associated with a specific slit of the parallax barrier. Figure 1 shows an SLM in which two pixel columns are associated with each slit of the parallax barrier.

Figure 2 of the accompanying drawings shows the angular zones of light created from an SLM and parallax barrier where the parallax barrier has a pitch  $b$  of an exact integer multiple of the pixel column pitch  $p$ . In this case, the angular zones coming from different locations across the display panel surface intermix and a pure zone of view for image 1 or image 2 does not exist. In order to address this, the pitch  $b$  of the parallax optic is reduced slightly so that the angular zones converge at the window plane 12 in

front of the display. This change in the parallax optic pitch is termed “viewpoint correction” and is shown in Figure 3 of the accompanying drawings. The viewing regions created in this way are roughly kite shaped.

For a colour display, each pixel is generally provided with a filter associated with one of the three primary colours. By controlling groups of three pixels each with a different colour filter, substantially all visible colours may be produced. In an autostereoscopic display, each of the stereoscopic image “channels” must contain sufficient of the colour filters for a balanced colour output. Many SLMs have the colour filters arranged in vertical columns, due to ease of manufacture, so that all the pixels in a given column have the same colour filter associated with them. If a parallax optic is used with such an SLM such that three pixel columns are associated with each slit (or lenslet), only one colour will be visible in each viewing region. This may be avoided using, for example, the techniques disclosed in EP 0 752 610.

The function of the parallax optic is to restrict the light transmitted through the pixels to certain output angles. This restriction defines the angle of view of each of the pixel columns behind a given slit. The angular range of view of each pixel is decided by the refractive index of the glass  $n$ , the pixel width  $p$  and the separation between the pixel and the parallax optic planes  $s$ , and is given by

$$\sin \alpha = n \sin \left( \arctan \left( \frac{p}{2s} \right) \right)$$

In order to increase the angle between viewing windows, it is necessary to either increase the pixel pitch  $p$ , decrease the gap between the parallax optic and the pixels  $s$ , or increase the refractive index of the glass  $n$ . Changing any of these variables is not easy. It is not always practical or cost effective to significantly change the refractive index of the substrate glass. Pixel pitch is typically defined by the required resolution specification of the panel and therefore cannot be changed. Additionally increasing pixel pitch requires a similar increase in the parallax barrier pitch which makes the barrier more visible, thus detracting from the final image quality. Decreasing  $s$  results

in manufacturing problems associated with making and handling thin glass. Therefore, it is difficult to use a standard parallax barrier to create 3D or multi-view displays with wide viewing angles.

One option for increasing the pixel pitch and therefore the viewing angle is to rotate the pixel configuration such that the colour subpixels run horizontally rather than vertically as described in JP7-28015. This results in a threefold increase in pixel width and therefore roughly three times increase in viewing angle. As mentioned, above this has the disadvantage that the barrier pitch increases as pixel pitch increases which in turn increases the visibility. The manufacture and driving of such a non-standard panel may not be cost effective. Additionally, there may be applications in which the increase in viewing angle needs to be greater than three times the standard configuration and therefore simply rotating the pixels may not be enough.

The window plane defines the optimum viewing distance of the display. An observer whose eyes are located in this plane will receive the best performance of the display. ~~As they move laterally in this plane, the image on the display will remain until they~~ reach the edge of the viewing region, whereupon the whole display will swiftly change to the next image as the eye moves into the adjacent viewing region. The line of the window plane within a viewing region is sometimes termed a "viewing window".

In an ideal display of the type shown in Figures 1, 2 and 3, the intensity distribution of light across each viewing window would be a "top hat" function. In other words, for each viewing window, the light intensity would be constant across the viewing window and zero outside the viewing window in the viewing plane. However, degradation of the window intensity distribution occurs so that the lateral and longitudinal viewing freedom of the observer is reduced compared with that illustrated in Figure 3. This can be caused by diffraction through the apertures as well as by gaps between pixels resulting in dark regions at the edges of the windows. In an ideal display, right eye image data would not be present in the left eye viewing region and vice versa. However, in practice, crosstalk occurs so that each eye can see some of the light intended for the other eye.

While a particular parallax element (slit or lenslet) is principally associated with one group of pixel columns, the adjacent groups of pixel columns will also be imaged by the element. Imaging of these groups creates lobes of repeated viewing regions to either side of the central, or zero order, lobe. These lobes repeat all the properties of the central lobe but are in general affected to a larger extent by the imperfections and aberrations of the optical system and will eventually become unusable as the lobe order increases. It is possible to use these higher order lobes in order to achieve a wider angle between windows. However, there will be a significant reduction in performance.

For example, by using a parallax optic having a pitch of  $b \sim 3p$ , it is possible to use windows A and C in Figure 4a of the accompanying drawings, for either 3D viewing or "dual view" where window B is either black or contains arbitrary data. While this gives an increased angle of view, the brightness is reduced to  $2/3$  of that produced by a barrier having a pitch  $b \sim 2p$  since every third pixel is "viewed" in an unused window. The increase in barrier pitch would increase the visibility of the barrier and the horizontal resolution would decrease. The windows are smaller than those of a two view system with the same viewing angle as illustrated in Figure 4b of the accompanying drawings, and therefore viewing freedom would be reduced. Another problem with this example is that, if the colour filters are arranged in RGB columns, then each window only sees one colour "subpixel".

Figure 5 of the accompanying drawings illustrates a parallax barrier with a slit width  $= 3p$  and spaced with a pitch  $b \sim 6p$ . This results in windows which are at a separation angle of three times that of a standard parallax barrier of pitch  $b \sim 2p$ . Because the slit width is  $3p$ , all three colour filters colours 15, 16 and 17 are seen in the same proportion. However this is only true at the exact centre of the viewing window as illustrated in Figure 5a of the accompanying drawings. As soon as the viewer moves away from the centre of the viewing window, the neighbouring image data 15a will be seen and crosstalk will occur as shown in Figure 5b of the accompanying drawings.



In order to reduce this crosstalk, the slit width can be reduced to less than  $3p$ . However, this results in an uneven colour balance. As shown in Figure 6a of the accompanying drawings, when the viewer is in the centre of the viewing window, the "white" pixel will appear light green because more of the green sub-pixel 16 is visible than each of the red and blue sub-pixels 15 and 17. Because of the reduced slit width, it is possible for the viewer to move away from the centre of the viewing window without seeing the neighbouring image data. However, the colour balance changes with angle of view and, as shown in Figure 6b, of the accompanying drawings for movement in one direction, the "white" pixel will now appear cyan.

Another way to achieve a larger separation angle would be to use the standard  $b \sim 2p$  barrier and use both secondary lobes A and D in Figure 7a of the accompanying drawings, which are separated by two window widths. This would have the same barrier visibility, brightness, and horizontal resolution as the two view system shown in Figure 7b of the accompanying drawings with the same angle. However, the viewing freedom would be significantly reduced.

---

Another known type of directional display is the rear parallax barrier display as shown in Figure 8 of the accompanying drawings. In this case, the parallax barrier 7, 8 is placed behind the SLM 1 to 5 i.e. between the SLM and the backlight. This arrangement has the advantage that the barrier is kept behind the SLM away from possible damage.

Lenticular screens are used to direct interlaced images to multiple directions, which can be designed to give a 3D image or give multiple images in multiple directions. Practical lenses tend to suffer from scatter and poor anti-reflection performance so that the surface is very visible in both ambient and backlit environments. Therefore, the image quality of lenticular screens can be poor and the system suffers from similar problems as parallax barriers such as the need for close proximity to the image pixels.

Holographic methods of image splitting also exist but they suffer from viewing angle problems, pseudoscopic zones and a lack of easy control of the images.

Micropolariser displays use a polarised directional light source and patterned high precision micropolariser elements aligned with the LCD pixels. Such a display offers the potential for high window image quality as well as 2D/3D function in a compact package. The dominant requirement is the incorporation into the LCD of micropolariser elements to avoid parallax issues.

US 6 424 323 discloses an image deflection system comprising a lenticular screen overlying a display device. The display is controlled to provide at least two independent images to be viewed from different viewing positions.

JP 7-28015 discloses the use of a patterned pixel shape with a lenticular barrier in which the windows formed by the display have a minimum crosstalk. Crosstalk is reduced by moving the relative positions of the pixels and appropriately arranging the spacing and orientation.

~~Other known types of multiple view displays are disclosed in WO 98/27451,~~  
DE 19822342 and JP H7-104212.

According to a first aspect of the invention, there is provided a parallax barrier comprising a plurality of groups of parallel slits, each group comprising  $N$  slits where  $N$  is an integer greater than 1, the slits of each group being spaced apart with a first pitch  $b1$  in a direction perpendicular to the slits and the groups being spaced apart with a second pitch  $b2$ , in the direction perpendicular to the slits, greater than  $N.b1$ .

The second pitch  $b2$  may be substantially equal to  $2.N.b1$ .

In one embodiment,  $N$  is equal to 2. In another embodiment,  $N$  is equal to 3.

According to a second aspect of the invention, there is provided a multiple view display comprising a barrier according to the first aspect of the invention and a spatial light modulator.

The modulator may comprise a plurality of columns of pixels extending parallel to the slits.

The columns may have a third pitch  $p$ , in a direction perpendicular to the longitudinal directions of the columns, which differs from the first pitch so as to provide viewpoint correction. The first pitch  $b1$  may be given by;

$$b1 = \frac{p}{1 \pm \frac{p}{e}}$$

where  $p$  is the pitch of the columns and  $e$  is the pitch of primary viewing windows produced by the display.

The columns may have a third pitch  $p$ , in a direction perpendicular to the longitudinal directions of the columns, which is greater than the first pitch.

The columns may comprise red, green and blue columns.

The columns may be arranged as repeating groups with each group being arranged in the order blue, red, blue, red, green, blue, green, blue, red; green, red, green.

The columns may be arranged as repeating groups with each group arranged in the order green, green, blue, blue, red, red.

The columns may be arranged as repeating groups of 18 with each group comprising three consecutive pairs of identical triplets, the orders of the colours of the triplets of the consecutive pairs being rolled by one position with respect to each other.

The columns may be arranged as repeating groups of 36 with each group comprising six consecutive pairs of identical triplets, the triplets of the consecutive pairs having orders comprising all permutations of red, green and blue.

The display may comprise a display driver for supplying image signals representing a plurality of views as interlaced columns to the modulator. The image signals may represent two views. The display may comprise an autostereoscopic display in which the image signals represent at least one pair of stereoscopic views.

It is thus possible to provide a parallax barrier which is suitable for use in multiple view displays having relatively wide viewing angles between viewing regions. Different embodiments of such displays may exhibit different advantages from among: reduced barrier visibility; reduced crosstalk between windows; improved viewing freedom; increased brightness; and improved colour matching.

The invention will be further described, by way of example, with reference to the accompanying drawings, in which;

Figure 1 is a diagrammatic horizontal cross-sectional view of a known type of multiple view display;

---

Figure 2 is a diagrammatic plan view illustrating angular viewing regions created by the display of Figure 1;

Figure 3 is a diagrammatic plan view illustrating viewpoint correction in the display of Figure 1;

Figure 4 illustrates diagrammatically at (a) and (b) two comparative examples of multiple view displays;

Figure 5 is a diagram illustrating visibility of pixel columns for on-centre viewing at (a) and for off-centre viewing at (b);

Figure 6 shows views similar to Figure 5 for a parallax barrier of reduced slit width;

Figure 7 shows views similar to Figure 4 for further comparative examples of multiple view displays;

Figure 8 is a diagrammatic cross-sectional plan view of a known type of rear parallax barrier multiple view display;

Figure 9 shows at (a) a diagrammatic cross-sectional plan view of a parallax barrier and display constituting an embodiment of the invention and at (b) a diagrammatic front view of the parallax barrier;

Figure 10 is a diagrammatic plan view of the display of Figure 9 illustrating the generation of viewing regions;

Figure 11 is a view similar to Figure 10 of another embodiment of the invention;

Figure 12 illustrates the visibility of columns of pixels in the display shown in Figure 11 for on-centre-viewing at (a) and for off-centre-viewing at (b);

Figure 13 illustrates a modification of the display shown in Figures 11 and 12 showing pixel column visibility for on-centre viewing at (a) and for off-centre viewing at (b);

Figure 14 illustrates colour sub-pixel arrangements on a panel and in left and right views for a display of the type shown in Figure 9 with three different orders of colour sub-pixels; and

Figure 15 shows views similar to Figure 14 for a display of the type shown in Figure 11;

Like reference numerals refer to like parts throughout the drawings.

The display shown in Figure 9 is a two view directional display which may be used as an autostereoscopic 3D display or as a display for providing two unrelated views to different observers. The display comprises a spatial light modulator in the form of an

LCD 20, for example of the type illustrated at 1 to 5 in Figure 1. The LCD 20 is pixellated and operates in transmissive mode so as to modulate light passing through the pixels from a backlight (now shown). However, other types of display may be used to modulate light in transmissive or reflective modes or to generate light within the display device itself (in the case of a front parallax barrier arrangement). The display also comprises a parallax barrier 21 disposed in front of the LCD 20, i.e. between the LCD 20 and the viewer or viewers. The barrier 21 may, for example, be embodied using standard emulsion techniques or retarder and polariser techniques or in any suitable way for providing regions such as 22 which are substantially opaque to light from the LCD 20 and slits such as 23 which are substantially transmissive to light from the LCD 20.

The LCD 20 is pixellated so as to form columns of pixels with a substantially uniform pitch  $p$  in a direction perpendicular to the longitudinal axes of the columns, which direction is generally horizontal during normal use of the display.

The slits of the barrier 21 are arranged non-periodically and extend parallel to the longitudinal axis of the pixel columns. In particular, the slits such as 23 are arranged in evenly spaced groups of slits with the slits in each group being evenly spaced. In the embodiment illustrated, each group comprises two slits with the slits in each group being spaced with a pitch  $b1$  which is similar to the pitch  $p$  of the pixel columns but differs therefrom so as to provide viewpoint correction as described hereinbefore. Thus, the pitch  $b1$  is slightly less than the pitch  $p$  for a front parallax barrier display of the type shown in Figure 9 but is slightly greater than the pixel column pitch  $p$  for a rear parallax barrier display of the type illustrated in Figure 8. In particular, in the case of a front parallax barrier, the pitch  $b1$  is given by,  $p/(1+(p/e))$  whereas, for a rear parallax barrier, the pitch  $b1$  is given by  $p/(1-(p/e))$ .

All of the groups of slits have the same number of slits with the same pitch  $b1$  and, in the embodiments shown, the slits extend throughout the height of the parallax barrier 21. The groups of slits are spaced apart in the direction perpendicular to the slits (horizontal during normal use of the display) by the same pitch  $b2$  which is equal to

four times the pitch  $bl$  and thus approximately equal to four times the pitch  $p$  of the pixel columns.

The display is driven by a display driver illustrated diagrammatically at 25 in Figure 9 such that image data for the two views which are to be displayed are interlaced as vertical stripes. The display driver 25 may be arranged to receive images for display and to interlace the data so as to ensure that the individual pixel columns display the correct vertical slices of the images. The display driver 25 may form part of the display or may be embodied partly or wholly within other apparatus, such as a computer, microprocessor or the like. The images may be captured "real" images or may be computer-generated. The images may form a stereoscopic pair for autostereoscopic 3D use of the display or may be stereoscopically unrelated, such as completely different viewpoint images of a game for two players or a series of cinematographic images for displaying a "movie" to one viewer and a satellite navigation image for another viewer, such as the driver of a vehicle.

---

As shown in Figures 9 and 10, the slits such as 23 of the barrier 21 are aligned with or adjacent the middle lines of the columns of pixels. In practice, the slits are offset from such mid-line alignment by a small amount so as to provide viewpoint correction. The display driver 25 supplies vertical image slices numbered 1 to 4 in Figure 10 to a group of four columns of pixels nearest each group of slits. The slits of the barrier 21 cooperate with the pixellation of the LCD 20 so as to define or create viewing regions labelled A to E in Figure 10. In each of the viewing regions, each group of slits restricts visibility of the columns of pixels such that two adjacent pixel columns only are visible to a viewer viewing the display from the viewing region. Thus, in the zero order lobe viewing region C, only those columns displaying image slices 2 and 3 are visible. Only the pixel columns displaying the image slices 1 and 2 are visible in the positive first order lobe viewing region D whereas only the pixels columns displaying the image slices 3 and 4 are visible in the negative first order lobe viewing zone B. Similarly, in the plus and minus second order lobe viewing regions E and A, only the pixel columns displaying the image slices 1 and 4 are visible.

The display driver 25 supplies the pixel image data to the LCD 20 such that the image slices 1 and 2 are provided from one of the images and the image slices 3 and 4 are provided from the other of the images. Thus, the first and second images forming the first and second views are visible in the viewing regions D and B, respectively. When providing autostereoscopic viewing, provided the left and right eyes of the observer are in the viewing regions B and D, respectively, a stereoscopic pair of images can be viewed correctly to provide the 3D effect. Conversely, a viewer whose eyes are in the viewing region D can see one of the images but not the other whereas a viewer whose eyes are in the region B can see the other image but not the first image.

The half angle  $\alpha$  subtending the centres of the viewing zones B and D at the display is given by;

$$\alpha = \sin^{-1} \left( n \sin \left( \tan^{-1} \frac{p}{s} \right) \right)$$

Compared with a conventional display of the type illustrated in Figures 1 to 3 and 4(a), the angle between the views is approximately doubled. In the case of an autostereoscopic display, this allows the optimum viewing distance or viewing window plane to be approximately half the distance away from the display compared with the conventional arrangement. Conversely, in the case of "unrelated" views, the angle between views or use with unrelated images is substantially increased.

The viewing regions to either side of the regions B and D which are actually used contain 50% of each image. Thus, the contribution to crosstalk from neighbouring viewing regions is reduced because 50% of the stray light is from the same image source. Compared with the three view arrangement illustrated in Figure 4(a), the display illustrated in Figures 9 and 10 makes use of 50% of the available light and each image is displayed by 50% of the pixels so that the horizontal resolution is 50% of the LCD resolution. In the case of the three view display of Figure 4(a), 33% of light is used and 33% of the LCD resolution is used by each image.



The display shown in Figure 11 differs from that shown in Figures 9 and 10 in the arrangement of the parallax barrier 21 and the image slices displayed by the LCD 20. In this embodiment, the barrier 21 comprises groups of three slits with the slits of each group having the same pitch  $b1$  as in the groups of slits in the display shown in Figures 9 and 10. However, the groups of slits are spaced with a horizontal pitch  $b2$  equal to six times the pitch  $b1$  and approximately equal to six times the pitch  $p$  of the pixel columns to within viewpoint correction. Also, each slit is aligned (to within viewpoint correction) with the boundary between a respective adjacent pair of pixel columns of the LCD 20.

Each group of pixel columns associated with each group of slits of the barrier 21 displays vertical image or view slices labelled 1 to 6 in Figure 11. The arrangement of the barrier 21 in relation to the pixel columns of the LCD 20 gives rise to the generation of viewing regions labelled A to G in Figure 11. In the first order viewing region D, the pixel columns displaying view slices 3, 4 and 5 are visible whereas, in the viewing region E, the pixel columns displaying the view slices 2, 3 and 4 are visible. In the viewing region C, the pixel columns displaying the view slices 4, 5 and 6 are visible whereas in the viewing region F, the pixel columns displaying the view slices 1, 2 and 3 are visible. In the viewing region B, the pixel columns displaying the view slices 5, 6 and 1 are visible whereas, in the viewing region G, the pixel columns displaying the view slices 6, 1 and 2 are visible. The display driver 25 supplies image data to the LCD 20 such that the view slices 4, 5 and 6 are of the first image whereas the view slices 1, 2 and 3 are of the second image. Thus, the first image is visible and the second image is substantially not visible in the viewing region C whereas the second image is visible and the first image is substantially not visible in the viewing region F. The half angle  $\alpha$  for the viewing regions C and F is given by;

$$\alpha_3 = \sin^{-1} \left( n \sin \left( \tan^{-1} \frac{3p}{2s} \right) \right)$$

which gives an angle between views which is approximately three times that for the display illustrated in Figure 4(a). Thus, for autostereoscopic display purposes, the

optimum viewing distance or viewing window plane is much nearer the display. Conversely, for viewing unrelated images, a greater separation of viewing regions is provided.

The windows to either side of each window used for viewing in the display of Figure 11 contain 66.7% of the same image data. Thus, the contribution to crosstalk from neighbouring windows is reduced because 66.7% of the stray light is from the same image source. 50% of the LCD resolution is used for each image and 50% of the available light is used for each image.

As shown in Figure 12, by using the pixel columns displaying the view slices 4, 5 and 6 for the first image and 1, 2 and 3 for the second image to display red, green and blue data, respectively, colour balanced is maintained. On-centre viewing of the red, green and blue pixel columns 15, 16 and 17, respectively, is illustrated at (a) in Figure 12. However, a major cause of crosstalk results from the outer edges of each group of slits because these are closest to pixel columns with opposite image data. When the viewer moves away from the centre of the viewing window, neighbouring image data is seen and crosstalk occurs as illustrated at (b) in Figure 12.

As illustrated in Figure 13, crosstalk may be reduced by reducing the widths of the slits and by reducing the slit pitch in each group of slits. On-centre viewing and off-centre viewing are illustrated at (a) and (b) in Figure 13 and correspond to the views shown at (a) and (b), respectively, in Figure 12. Although the reduced slit width reduces the light output of the display, crosstalk effects are reduced while permitting greater lateral freedom of movement of the or each viewer. Although the pitch of the slits in each group is reduced in the arrangement of Figure 13 as compared with the arrangement of Figure 12, the pitch of the groups of slits is unchanged.

Figure 14(a) illustrates the use of an LCD 20 of conventional type in which "white" pixels are divided into repeating groups of colour sub-pixels. In particular, the pixel columns of each group of three columns are provided with red, green and blue filter strips so that all of colour sub-pixels in each column display the same colour and

adjacent pairs of columns display different colours with the pattern red (R), green (G) and blue (B) repeating across the display. As illustrated for the right and left views, although the correct colour balance is obtained for such an arrangement, there is a substantial non-uniformity in the spacing of single colours for each view. In particular, as highlighted in Figure 14(a), the spacing of red sub-pixels alternates between 9 and 3 colour sub-pixels. Such uneven spacing can be very visible especially for low resolution displays, and therefore detracts from image quality. Also, for each view, the ordering of the colour sub-pixels does not follow the same repeating pattern of three colour sub-pixels. For example, in the right view, the first white pixel is made up of R, G and B sub-pixels but the actual ordering is of R, G, G and B colour sub-pixels. Thus, one of the G sub-pixels belongs to another white pixel and such crossing over in the ordering of the components of each white pixel can lead to further undesirable image artefacts.

In order to avoid or reduce these problems, the colours of the pixel columns may be changed from the standard repeating RGB arrangement and examples of alternative arrangements are illustrated in Figure 14 at (b) and (c). In Figure 14 at (b), the colour order of the columns is changed to a repeating pattern of GBBRBRGBGBRGRG. The colour sub-pixels for each view are thus arranged as repeating groups of RGB sub-pixels so that there is no crossing over in the ordering of components of white pixels. Further, the spacing of individual colour sub-pixels in each view alternates between 5 and 7 sub-pixel, which improves the uniformity of spacing and hence the image quality.

A disadvantage of such an arrangement is that, if the display is also required to operate in a 2D mode, the sub-pixel ordering reverts to that of the actual LCD 20 and is no longer arranged as repeating groups of three colour sub-pixels. This would result in some crossing over of the ordering of the components of the white pixels and would again lead to undesirable image artefacts. However, such a compromise may be acceptable because, in the 2D mode, the full spatial resolution of the LCD is used and this helps to reduce the visibility of crossover effects.

Another advantage of the arrangement shown at (b) in Figure 14 is achieved in the autostereoscopic 3D application of such a display. In this case, 3D pixels with zero disparity, i.e. appearing at the same position on the display to both left and right eyes, have a residual disparity of only two sub-pixels. This represents an improvement over the arrangement illustrated at (a) in Figure 14, in which the residual disparity is 6 sub-pixels either in the same direction or alternating between in front of the screen and behind the screen.

A further arrangement of colour sub-pixels is illustrated at (c) in Figure 14. In this case, each colour component is repeated so that the columns are arranged as pairs with each pair displaying the same colour component. This arrangement avoids crossover artefacts in the multiple view mode and provides more even spacing of colour components for the two views. When used in the 2D mode, the display is used with half of the spatial resolution of the LCD 20 but there is no crossing over of the components of white pixels. Such an arrangement may be used, for example, in displays with high resolution or for dual view displays where the basic resolution of the LCD has been increased to give each viewer a high resolution image.

---

In the embodiments illustrated in Figures 12 to 13, the ordering of the colours is that of a conventional RGB LCD 20 as illustrated at (a) in Figure 15. The undesirable colour artefacts which would be visible using a single wide slit with a pitch substantially equal to 6 pixel column pitches are thus avoided. However, if an error occurred during manufacture in the pitch, width or spacing of such slits, then some colour artefacts might remain. In the arrangement shown at (a) in Figure 15, if the ratio of the contributions of each group of three adjacent RGB pixel columns is not equal, then white balance is not obtained. If this error occurs for each group of RGB pixel columns, the error will propagate across the whole display.

An alternative sequence of colour sub-pixels is illustrated at (b) in Figure 15 to avoid or reduce the effects of this problem. In this arrangement, the order of the colour sub-pixels is "rolled" by one position for each group of sub-pixels in each view. This pattern repeats for every three groups so that, provided the LCD 20 has a sufficiently

high resolution, any errors will average out across the panel and will be less visible or invisible to the viewer. However, the spacing of individual colour sub-pixels in each view varies with a pattern of 5, 5 and 8 pixels and may result in undesirable image artefacts.

A further arrangement is illustrated at (c) in Figure 15 to overcome or reduce the effects of errors and to provide more even colour sub-pixel spacings. In this arrangement, the ordering of two neighbouring colour sub-pixels is swapped whereas the third is kept in the same position. This pattern repeats every six groupings. Thus, although errors are not averaged out as efficiently as in the arrangement shown at (b) in Figure 15, the spacings of individual colour sub-pixels varies with a pattern of 7, 7, 6, 5, 5, 6 pixels and is therefore less visible.

---

**CLAIMS:**

1. A parallax barrier comprising a plurality of groups of parallel slits, each group comprising  $N$  slits where  $N$  is an integer greater than one, the slits of each group being spaced apart with a first pitch  $b1$  in a direction perpendicular to the slits and the groups being spaced apart with a second pitch  $b2$ , in the direction perpendicular to the slits, greater than  $N.b1$ .
2. A barrier as claimed in claim 1, in which the second pitch  $b2$  is substantially equal to  $2.N.b1$ .
3. A barrier as claimed in claim 1 or 2, in which  $N$  is equal to 2.
4. A barrier as claimed in claim 1 or 2, in which  $N$  is equal to 3.
5. A multiple view display comprising a barrier as claimed in any one of the preceding claims and a spatial light modulator.
6. A display as claimed in claim 5, in which the modulator comprises a plurality of columns of pixels extending parallel to the slits.
7. A display as claimed in claim 6, in which the columns have a third pitch  $p$ , in a direction perpendicular to the longitudinal directions of the columns, which differs from the first pitch so as to provide viewpoint correction.
8. A display as claimed in claim 7, in which the first pitch  $b1$  is given by:

$$b1 = \frac{p}{1 \pm \frac{p}{e}}$$

where  $p$  is the pitch of the columns and  $e$  is the pitch of primary viewing windows produced by the display.

9. A display as claimed in claim 6, in which the columns have a third pitch  $p$ , in a direction perpendicular to the longitudinal directions of the columns, which is greater than the first pitch.

10. A display as claimed in any one of claims 6 to 9, in which the columns comprise red, green and blue columns.

11. A display as claimed in claim 10 when dependent on claim 3, in which the columns are arranged as repeating groups with each group arranged in the order blue, red, blue, red, green, blue, green, blue, red, green, red, green.

12. A display as claimed in claim 10 when dependent on claim 3, in which the columns are arranged as repeating groups with each group arranged in the order green, green, blue, blue, red, red.

~~13. A display as claimed in claim 10 when dependent on claim 4, in which the~~  
columns are arranged as repeating groups of 18 with each group comprising three consecutive pairs of identical triplets, the orders of the colours of the triplets of the consecutive pairs being rolled by one position with respect to each other.

14. A display as claimed in claim 10 when dependent on claim 4, in which the columns are arranged as repeating groups of 36 which each group comprising six consecutive pairs of identical triplets, the triplets of the consecutive pairs having orders comprising all permutations of red, green and blue.

15. A display as claimed in any one of claims 5 to 14, comprising a display driver for supplying image signals representing a plurality of views as interlaced columns to the modulator.

16. A display as claimed in claim 15, in which the image signals represent two views.

⌂

17. A display as claimed in claim 15 or 16, comprising an autostereoscopic display in which the image signals represent at least one pair of stereoscopic views.
-



**ABSTRACT**  
**PARALLAX BARRIER AND MULTIPLE VIEW DISPLAY**


(Figure 9)

A parallax barrier (21) comprises evenly spaced groups of slits (23). Each group comprises two or more slits which are evenly spaced and the groups are spaced with a period which is greater than the product of the number of slits in each group and the slit period in each group. Such a barrier (21) may be used with a spatial light modulator (20) having columns of pixels whose structure cooperates with the barrier structure to provide a wider angle between views in a multiple view display, such as an autostereoscopic 3D display or a display providing two or more different views to two or more observers.

---


**THIS PAGE BLANK (USPTO)**

Figure 1




**THIS PAGE BLANK (USPTO)**

Figure 2



**THIS PAGE BLANK (USPTO)**

Figure 3




**THIS PAGE BLANK (USPTO)**




Figure 4

(a)




(b)




**THIS PAGE BLANK (USPTO)**

Figure 5



(a)




(b)

crosstalk

**THIS PAGE BLANK (USPTO)**


Figure 6




**THIS PAGE BLANK (USPTO)**

Figure 7

(a)




(b)



**THIS PAGE BLANK (USPTO)**






Figure 8




**THIS PAGE BLANK (USPTO)**

Fig 9




**THIS PAGE BLANK (USPTO)**

Figure 10



**THIS PAGE BLANK (USPTO)**


Figure 11



**THIS PAGE BLANK (USPTO)**




Figure 12




**THIS PAGE BLANK (USPTO)**

Figure 13





(a)



(b)


**THIS PAGE BLANK (USP 10)**

20




**THIS PAGE BLANK (USPTO)**

Panel



(c) Right




Left




**THIS PAGE BLANK (USPTO)**






Figure 15




(a) Right







Left







Panel



(b) Right



Left



**THIS PAGE BLANK (USPTO)**

---

[illegible]

20 →

RGB

G	B	R
6	5	7

6	5	7
B	R	G

P	C	B
---	---	---

6 5 7

G	R	B
---	---	---

5	7	6
B	G	R

5	7	6
R	B	G

Left

**THIS PAGE BLANK (USPTO)**